# This Page Is Inserted by IFW Operations and is not a part of the Official Record

# **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

# IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.



WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT) WO 99/58228 (51) International Patent Classification 6: (11) International Publication Number: A1 B01D 53/64, 53/60 (43) International Publication Date: 18 November 1999 (18.11.99) (81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, PCT/CA99/00403 (21) International Application Number: BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, 3 May 1999 (03.05.99) (22) International Filing Date: LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO (30) Priority Data: patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), US 8 May 1998 (08.05.98) 60/084,762 Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, (71) Applicant (for all designated States except US): ISCA MAN-BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, AGEMENT LTD. [CA/CA]; 505-2320 West 40th Avenue, TD, TG). Vancouver, British Columbia V6M 4H6 (CA). (72) Inventors; and **Published** (75) Inventors/Applicants (for US only): CALDWELL, Douglas With international search report. [CA/CA]; 505-2320 West 40th Avenue, Vancouver, British Columbia V6M 4H6 (CA). BIGGAR, John, W. [CA/CA]; 4648 Brentlawn, Burnaby, British Columbia V5C 3V2 (CA). MCINTYRE, Brian, W. [CA/CA]; 105-621 East 6th Avenue, Vancouver, British Columbia V5T 4H3 (CA). (74) Agent: OYEN, Gerald, O., S.; Oyen Wiggs Green & Mutala, The Station, 601 West Cordova Street #480, Vancouver, British Columbia V6B 1G1 (CA). (54) Title: MERCURY REMOVAL FROM FLUE GAS

#### (57) Abstract

Chlorine is injected in a gaseous or liquid form into a hot (greater than 100 °C) gas stream for the purpose of oxidizing objectionable components in the gas stream, such as, but not restricted to, SO<sub>2</sub>, NO<sub>x</sub> and mercury, when the oxidized form of the components is more readily removed from the gas stream.

#### FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL A	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM .	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT .	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU .	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ .	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA :	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG :	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA (	Canada	ſT	Italy	MX	Mexico	^ UZ	Uzbekistan
CF (	Central African Republic	JP	Јарап	NE	Niger	VN	Vict Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH :	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM (	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE (	Germany	LI	Liechtenstein	SD	Sudan		
DK :	Denmark	LK	Sri Lanka	SE	Sweden		
EE :	Estonia	LR	Liberia	SG	Singapore		

5

WO 99/58228 PCT/CA99/00403

#### MERCURY REMOVAL FROM FLUE GAS

#### FIELD OF THE INVENTION

The present invention relates to simultaneous oxidation of SO<sub>2</sub> to sulphuric acid, NO<sub>x</sub> to nitric acid, and metallic mercury vapour to a mercury chloride, in a flue gas, thereby allowing capture of mercury in the downstream process solutions.

## 10 BACKGROUND OF THE INVENTION

U.S. Patent No. 4,619,608, granted October 28, 1986, describes the effects of sulphur dioxide and nitrogen oxides released from the burning of fossil fuel.

15

20

25

Regulations in force since 1985 have mandated two stages of cleanup for the flue gases emitted from fossil fuel powered utility power stations. A December, 1996 proposal by the U.S. Environmental Protection Agency (EPA) has proposed even higher control levels based on health concerns.

In addition, mercury has now become a pollutant of concern.

Costs of capturing mercury can run as high as \$100,000 per pound using activated carbon or limestone systems. A problem with the limestone systems is the re-release of the mercury once captured.

In February, 1998, the EPA released a mercury report to U.S. Congress which identified the health concerns and the need to

PCT/CA99/00403

e e

WO 99/58228

develop new technologies to capture mercury from the vapour emitted from coal fired power plants.

- 2 -

#### **SUMMARY OF THE INVENTION**

5

U.S. Patent No. 4,619,608 describes a process for injecting chlorine to oxidize SO<sub>2</sub> and NO<sub>x</sub> components of a flue gas stream, and removing them from the flue gas.

10

15

20

25

This invention is an improvement on that process and adds the capacity of trapping metallic mercury in a form that avoids the potential for re-release of the mercury. Costs to operate any system are a concern, and the process herein described is more economical than existing technology. The innovation is in the combination of the capture of all three pollutants of concern, namely SO<sub>2</sub>, NO<sub>x</sub> and Hg vapour, in one single economical process.

The invention is directed to a process for oxidizing gaseous pollutants in a flue gas stream composed of flue gases, water vapour and one or more gaseous pollutants selected from the group consisting of SO<sub>2</sub>, NO, NO<sub>2</sub>, NO<sub>x</sub>, H<sub>2</sub>S, and mercury vapour, said oxidized form of the pollutants being more readily removable from the flue gas stream by water absorption than the non-oxidized form thereof, comprising: (a) injecting sufficient chlorine in a gaseous form, a liquid form, or as a water solution, into the flue gas stream while the flue gas stream is at a temperature greater than 100°C to thereby react the chlorine with the pollutants and permitting the flue gas stream/chlorine mixture to react for

20

a sufficient time to enable a significant amount of oxidation of the pollutants to occur, whereby an oxidized flue gas stream comprising flue gases, water vapour and one or more gaseous oxidized said pollutants is formed; (b) scrubbing the oxidized flue gas stream with water, or water solution, of pH less than or equal to 7; and (c) adding sufficient alkali metal halogen salt to precipitate mercuric iodide from the water or water solution of pH less than or equal to 7, as the concentration level requires. The alkali metal halogen salt can be potassium iodide.

#### 10 DETAILED DESCRIPTION OF THE INVENTION

Chlorine is injected in a gaseous liquid or solution form into a hot gas stream of a temperature greater than 100°C for the purpose of oxidizing objectionable components in the gas stream, such as, but not restricted to SO<sub>2</sub>, NO<sub>x</sub>, and mercury vapour, when the oxidized form of the gases is more readily removed from the gas stream. After sufficient reaction time, the gas stream mixture passes through water scrubbers for the further removal of the objectionable components from the gas stream. Acidic and basic compounds of the gas stream and halogens, including excess chlorine, are also removed in the scrubbers. The pollutants remain as the corresponding oxidized acids or salts in the process effluent solution. The mercury is precipitated from the process solution.

Chlorine can be used to remove mercury from gases, as described by British Patent No. 1,121,845, and U.S. Patent No. 3,849,267. In these cases, the mercury is converted to mercuric chloride

that is captured in solution. The subject matter of these two patents is incorporated herein by reference.

The "Mechanism and Kinetics of Mercury Oxidation", by

Chlorine-Containing Solutions" (V.A. Skripnik et al. - J. Appl. Chem.

USSR, 52, 1169 (1979) - Plenum Publishing) clearly demonstrates that the oxidation of the mercury with chlorine occurs in the gas phase. In investigating the process of purifying a gas from mercury with chlorine water, they found that sweeping out of chlorine from the water takes place simultaneously with the removal of mercury from the gas. Practically all of the chlorine (90%) is swept into the gas phase, where the oxidation of mercury also takes place. The higher the chlorine concentration of the arriving water and the higher its circulation rate, that is, the greater the amount of chlorine swept out, the less is the metallic mercury content of the purified gas.

The process of purifying the gas from mercury with an acidic chlorine-containing solution can be represented by two mechanisms:

- (1) Chlorine from the solution is evacuated into the gas space and reacts with the mercury;
- (2) Mercury diffuses from the gas phase into the solution and reacts with the chlorine.

Each of these mechanisms consists of individual stages, and
has limiting stages which determine the rate of the given mechanism and
of the entire process as a whole. The studies performed showed that
practially all the chlorine is swept out of the solution into the gas phase,

10

15

and this process takees place at a high rate. This means that purification of the gas from mercury takes place principally by the first mechanism, that is, in the gas phase, with subsequent absorption of the reaction products by the solution. This process includes the following stages: diffusion of chlorine in the solution, sweeping out of the chlorine from the solution into the gas space, diffusion of chlorine and mercury in the gas phase, reaction of chlorine with the mercury, and extraction of the reaction products into the solution. The chlorine-containing solution is more reactive with respect to mercury in acid medium than in alkaline medium. The subject matter of this article is incorporated herein by reference.

Recent work by Argonne Laboratories and others has confirmed that the use of chlorine is the most effective way to capture mercury that is in the metallic form (Feely, Thomas J. III, "An Overview of the U.S. Department of Energy's Electric Utility Mercury Emissions R&D Activities" Acid Rain and the Electric Utilities II Conference, Jan. 21-22, 1997, Scottsdale, AZ.

Much current attention has been focused on mercury, due primarily to its ability to persist in the environment and to bioaccumulate, in the form of methyl mercury, in the food chain. Mercury has been shown to be present in flue gas produced by coal combustion, but at extremely low concentrations, on the order of parts per billion. This, coupled with the fact that mercury can be associated with very fine particles or can exist as a vapour in coal-fired power systems, makes it difficult to remove by conventional pollution control equipment. To

10

15

further complicate matters, the chemical form (or oxidation state) of mercury not only impacts its collection or removal but also its transport and subsequent deposition once released to the atmosphere. It is known that coal-combustion mercury exists as a vapour in both the elemental (Hg°) and ionic or oxidized (Hg++) form. Therefore, in addition to determining the split of mercury between the solid and gaseous phase, it is also necessary to measure its state of oxidation. The results of characterization studies indicate that gaseous-state mercury predominates in most coal-fired boiler flue gases. Typically, greater than 90% of the mercury is collected as a vapour. The subject matter of this article is also incorporated herein by reference.

In the case of the subject invention, the use of chlorine to oxidize  $SO_x$  and  $NO_x$  in a flue gas also results in the conversion of the metallic mercury to mercuric chloride. This mercuric chloride is captured in the sulphuric acid solution that results from the conversion of  $SO_2$  to  $H_2SO_4$ .

Using a small holding tank, the mercury is precipitated out according to the following reaction steps:

(i) 
$$2KI + 2H_2SO_4 \longrightarrow 2KHSO_4 + SO_2 + 2H_2O$$

(ii) 
$$I_2 + I^2 - I_3^2$$

(iii) 
$$Hg^{2+} + 2I_3^{-}$$
 -->  $HgI_2 + 2I_2$ 

25

Plate and frame filter presses, or other methods, can then be used to remove the filter cake.

As will be apparent to those skilled in the art in the light of the foregoing disclosure, many alterations and modifications are possible in the practice of this invention without departing from the spirit or scope thereof. Accordingly, the scope of the invention is to be construed in accordance with the substance defined by the following claims.

10

15

#### WHAT IS CLAIMED IS:

- 1. A process for oxidizing gaseous pollutants in a flue gas stream composed of flue gases, water vapour and one or more gaseous pollutants selected from the group consisting of SO<sub>2</sub>, NO, NO<sub>2</sub>, NO<sub>x</sub>, H<sub>2</sub>S, and mercury vapour, said oxidized form of the pollutants being more readily removable from the flue gas stream by water absorption than the non-oxidized form thereof, comprising:
- (a) injecting sufficient chlorine in a gaseous form, a liquid form, or as a water solution, into the flue gas stream while the flue gas stream is at a temperature greater than 100°C to thereby react the chlorine with the pollutants and permitting the flue gas stream/chlorine mixture to react for a sufficient time to enable a significant amount of oxidation of the pollutants to occur, whereby an oxidized flue gas stream comprising flue gases, water vapour and one or more gaseous oxidized said pollutants is formed;
  - (b) scrubbing the oxidized flue gas stream with water, or water solution, of pH less than or equal to 7; and
- (c) adding sufficient alkali metal halogen salt to precipitate
  the mercury from the water or water solution of pH less than or equal to
  7, as the concentration level requires.
  - 2. A process as claimed in claim 1 wherein the alkali metal halogen salt is potassium iodide.

## INTERNATIONAL SEARCH REPORT

Inte ional Application No PCT/CA 99/00403

A. CLASSII	FICATION OF SUBJECT MATTER B01D53/64 B01D53/60		
According to	o International Patent Classification (IPC) or to both national classific	eation and IPC	
	SEARCHED  cumentation searched (classification system followed by classificat	ion symbols)	· · · · · · · · · · · · · · · · · · ·
IPC 6	BO1D	WI SYNDOISY	
	tion searched other than minimum documentation to the extent that	such documents are included in the fields se	earched
Documentat	tion searched other than maintain cocumentation to the extent tion.		
Electronic d	ata base consulted during the international search (name of data ba	ase and, where practical, search terms used	)
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the re	levant passages	Relevant to claim No.
X	EP 0 208 036 A (TOKYO METROPOLIT ENVIRONMENT) 14 January 1987 (19	AN 87-01-14)	1
	page 5, paragraph 2 page 6 - page 7		
	page 9 page 11		
	page 12, paragraph 2 page 13, paragraph 1; figures 1	,4	
A	WO 98 16301 A (THOMASSEN THOMAS) 23 April 1998 (1998-04-23)		1
	page 1, line 5 - line 12 page 1, line 28 - line 35		
	page 3, line 29 - page 4, line page 9, line 18 - page 10, line	5 2· claims	
	1-5; figure 1	2, 0.4	
		-/	
	·		
			17
X Furt	ther documents are listed in the continuation of box C.	χ Patent family members are listed	) in annex.
° Special c	ategories of cited documents :	"T" later document published after the into	emational filing date
consi	nent defining the general state of the art which is not idered to be of particular relevance	cited to understand the principle or the invention	
filing		"X" document of particular relevance; the cannot be considered novel or canno involve an inventive step when the de	it be considered to
which	rent which may throw doubts on priority claim(s) or h is cited to establish the publication date of another on or other special reason (as specified)	"Y" document of particular relevance; the cannot be considered to involve an in	claimed invention eventive step when the
"O" docun	nent referring to an oral disclosure, use, exhibition or r means	document is combined with one or m ments, such combination being obvious in the art.	ore other such docu-
"P" docum	nent published prior to the international filing date but than the priority date claimed	"&" document member of the same patent	t family
Date of the	e actual completion of the international search	Date of mailing of the international se	earch report
	6 August 1999	13/08/1999	· · · · · · · · · · · · · · · · · · ·
Name and	d mailing address of the ISA European Patent Office, P.B. 5818 Patentiaan 2	Authorized officer	÷
	NL - 2280 HV Rijawijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Cubas Alcaraz, J	

1

#### INTERNATIONAL SEARCH REPORT

Int. tional Application No PCT/CA 99/00403

	ation) DOCUMENTS CONSIDERED TO BE RELEVANT	Relevant to daim No.		
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to daim No.		
A	US 4 619 608 A (MCINTYRE BRIAN W ET AL) 28 October 1986 (1986-10-28) cited in the application the whole document	1,2		
A	DE 44 22 661 A (PATRA PATENT TREUHAND) 4 January 1996 (1996-01-04) column 1, line 55 - column 2, line 15; claims 1-21	2		

1

## INTERNATIONAL SEARCH REPORT

information on patent family members

Inte ional Application No PCT/CA 99/00403

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
EP 0208036	0208036 A 14-01-1987		JP 1440770		c 30-05-1988
			JP	61222525 A	03-10-1986
			JP	62047572 B	08-10-1987
			AT	47532 T	15-11-1989
			CA	1233965 A	15-03-1988
			US	4729882 A	08-03-1988
WO 9816301	Α	23-04-1998	NO	970306 A	16-04-1998
US 4619608	Α	28-10-1986	AT	8 <b>976</b> 3 T	15-06-1993
			CA	1259165 A	12-09-1989
			DE	3688496 A	01-07-1993
			DE	3688496 T	16-12-1993
			EP	0220075 A	29-04-1987
DE 4422661	A	04-01-1996	CA	2150529 A	29-12-1995